

RL5000



*RL5000 with
high-topper*

So many choices. Perfectly suited for any location. The Triton RL5000.

One of our most customizable machines yet, the Triton RL5000 will change the way you think about ATMs. With a stunning 10.4-inch LCD screen, the RL5000 allows for a remarkable array of colorful, branded content. Logos, photos, and custom graphics of all kinds are quickly and easily integrated, using the simple-to-operate PC-based interface. At the heart of this almost endlessly configurable system is the user-friendly Microsoft® Windows® CE 5.0 operating system, powered by the Intel X2® processor.

The machine's sleek profile helps the RL5000 sit attractively in any location, from C-store to bar to hotel lobby. The incredibly sturdy and

durable construction, and a range of high-precision vault and lock options combine to make the RL5000 secure in any setting. Likewise, multiple dispenser choices are available to match the traffic of your location.

The Triton RL5000. It's endless customization, for an endless supply of user options. And as always, it's a Triton. So it's reliable, easy to service and maintain, and fully compliant.



RL5000
with high-
topper

RL5000

In Detail

The future of ATMs is here.

FEATURES:

- 10.4" (264 mm) VGA color display with 640 x 480 resolution
- One to four cassettes
- 80 mm thermal printer with presenter
- Triton Connect™ compatible
- 2 MB journal storage (32,768 records)
- Dip-style card reader; optional dip EMV smart card reader, optional EMV motorized card reader (Track 1,2,3 Read), or EMV motorized card reader/encoder (Track 1,2,3 Read, Track 3 write)
- Americans with Disabilities Act (ADA) compliant and audio compliant
- Encrypting PIN Pad (EPP) to comply with all international encryption standards, PCI compliant
- UL 291 Business Hours cabinet or optional UL 291 Level 1 Safe
- Electronic lock or optional Kaba Mas Cencon lock
- Multi-lingual capabilities
- Dial-up 56k baud internationally certified modem and TCP/IP communications; optional wireless
- Dimensions:
 - Width: 16.9" (429 mm)
 - Depth: 25.6" (650 mm)
 - Height: 54.3" (1390 mm) without topper
 - Height: 64.9" (1648 mm) with mid-topper
 - Height: 77.8" (1976 mm) with high-topper
- Weight: 245 lb (111 kg) weight varies with options

Advertising revenue potential:

- Decals and signage
- Couponing
- Display graphics

TECHNICAL SPECS:

- RISC microprocessor
- Microsoft Windows® CE 5.0
- 128 MB flash memory, expandable
- 128 MB RAM
- Six USB master ports
- One compact FLASH socket
- Five serial ports


OPERATING SPECS:

- Temperature:
 - 10° to 40° C / 50° to 104° F
- Relative humidity:
 - 20% to 80% non-condensing
- Power consumption:
 - 2.0 A @ 115 VAC at 60 Hz
 - 1.0 A @ 230 VAC at 50 Hz

Triton Headquarters • 522 East Railroad Street
Long Beach, Mississippi 39560 USA
With offices throughout the U.S. and worldwide
including Canada, UK, Australia, and Hong Kong
Phone: 1-228-868-1317 • Toll free: USA & Canada 1-800-367-7191
www.triton.com • Email: sales@triton.com

© 2008 Delaware Capital Formation, Inc. All Rights Reserved. TRITON, TRITON WHERE MONEY COMES FROM, DOVER and DOVER logo are registered trademarks of Delaware Capital Formation, Inc., a wholly-owned subsidiary of Dover Corporation.

Current as of 2/08 · RL5000 product sheet-07203-00034



The dimensions shown comply with U.S. Federal ADA guidelines. For installation within the U.S., be sure to check state and local guidelines for complete compliance. For non-USA installations, check regulations for the country in which the machine will be installed.

**specifications subject to change without notice*

ATM INSTALLATION SPACE REQUIREMENTS FOR ADA COMPLIANCE